

GAS20...GAS160



Model No.	Dimension (mm)											Load kN		Weight ≈kg	Inventory
	d	B	C1	d2	G	d4	L7	L3 min	d5	h1	L4	Load ratings	Load ratings		
												kN/Dynamic	kN/Static		
GAS20	20	16	23	56	M18×2	28	25	30	48	65	95	48	82	0.42	√
GAS25	25	20	23	56	M18×2	28	25	30	48	65	95	63	82	0.57	√
GAS30	30	22	28	64	M24×2	34	30	35	56	75	109	82.7	122	0.91	√
GAS35	35	25	30	78	M30×2	45	40	40	66	90	132	107	177	1.9	√
GAS40	40	28	35	94	M39×3	56.5	45	48	78	105	155	135	287	3	√
GAS50	50	35	40	116	M50×3	70	55	66	89	135	198	210	422	4.9	√
GAS60	60	44	50	130	M64×3	87	65	84	118	170	240	234	522	7.5	√
GAS70	70	49	55	154	M80×3	110	75	110	128	195	278	431	707	11.5	√
GAS80	80	55	60	176	M90×3	128	80	120	156	210	305	554	870	16.5	√
GAS90	90	60	65	210	M100×3	152	90	140	168	250	365	671	1284	35.5	√
GAS100	100	70	70	230	M110×4	170	105	150	171	275	400	842	1460	43.5	√
GAS110	110	70	80	264	M120×4	180	115	160	189	300	442	910	2024	60.5	√
GAS120	120	85	90	340	M150×4	210	140	190	243	360	540	1336	2970	96.5	√
GAS140	140	90	110	380	M160×4	230	185	200	248	420	620	1665	3500	138	○
GAS160	160	105	110	480	M180×4	260	200	220	273	460	710	1935	4302	209	○