

# LMB...UU..OP Series

Resin retainer										Major dimensions and tolerance										Eccentricity		Radial clearance		Back lead (relief%)												
LMB..UU	Trọng lượng Kg	LMB..UU-AJ	Ball diameter	Weight	LMB..UU-OP	Trọng lượng Kg	Inch	mm	mm	Precision(Inch)	Precision(gm)	Height(Inch)	Height(gm)	D(Inch/mm)	D Tolerance (±0.001)	D Tolerance (±0.002)	L Tolerance(Inch)	L Tolerance(gm)	B Tolerance(Inch)	B Tolerance(gm)	W(Inch/mm)	D1(Inch/mm)	h(Inch/mm)	h1(Inch/mm)	Ø	Precision	High	Radial clearance (µm)	Dynamic	Static						
LMB4	4	8	LMB4-AJ	4	7.5	—	—	14	6.35	0.25	6.35	0.0025	0.6	0.0040	0.9	500012.700	0.0045	0.11	750019.050	0.008	0.200	511012.98	0.008	0.200	0.0300.992	468701.906	0.61	—	—	0.0038	0.00512	-0.00113	206	265		
LMB8UU	4	14	LMB8UU-AJ	4	13.5	—	—	30	9.525	0.375	9.525	0.0025	0.6	0.0040	0.9	425015.875	0.0050	0.13	875022.225	0.008	0.200	435816.15	0.008	0.200	0.0300.992	588014.935	0.61	—	—	0.0038	0.00512	-0.00113	225	314		
LMB10UU	4	37	LMB10UU-AJ	4	38.5	LMB10UU-OP	3	28	12	0.5	12.7	0.0025	0.6	0.0040	0.9	875022.225	0.0050	0.13	1250021.750	0.008	0.200	962524.46	0.008	0.200	0.0300.992	820920.853	0.615	34.7	9375	80°	0.0038	0.00512	-0.00113	510	784	
LMB16UU	4	76	LMB16UU-AJ	4	74	LMB16UU-OP	3	57	58	15.875	0.625	15.875	0.0025	0.6	0.0040	0.9	1125028.575	0.0050	0.13	1500038.100	0.008	0.200	1103028.04	0.008	0.200	0.0300.992	1059026.899	0.615	37.5	9525	80°	0.0038	0.00512	-0.00113	774	1180
LMB20UU	5	95	LMB20UU-AJ	5	93	LMB20UU-OP	4	76	34	19.05	0.75	19.05	0.0030	0.7	0.0040	0.10	317501.2500	0.0065	0.16	1625041.275	0.008	0.200	1165029.61	0.008	0.200	0.0300.992	1176029.870	0.615	43.75	11125	60°	0.00410	0.00615	-0.00248154	862	1370
LMB24UU	6	200	LMB24UU-AJ	6	198	LMB24UU-OP	5	170	1	25.4	1	25.4	0.0030	0.7	0.0040	0.10	396881.5625	0.0065	0.16	2250057.150	0.012	0.300	1754744.57	0.012	0.300	0.06791.727	1468707.306	0.615	56.25	142875	50°	0.00410	0.00615	-0.00248154	980	1570
LMB28UU	6	440	LMB28UU-AJ	6	430	LMB28UU-OP	5	370	1-14	31.75	1.25	31.75	0.0035	0.8	0.0050	0.12	508802.0000	0.0075	0.19	2625066.675	0.012	0.300	2004755.92	0.012	0.300	0.06791.727	1885947.904	1.025	62.5	15875	50°	0.00512	0.00820	-0.0038	1570	2740
LMB32UU	6	670	LMB32UU-AJ	6	660	LMB32UU-OP	5	570	1-12	38.1	1.5	38.1	0.0035	0.8	0.0050	0.12	603252.3750	0.0075	0.19	3000076.200	0.012	0.300	2411861.26	0.012	0.300	0.08502.184	2338956.870	1.23	75	1985	50°	0.00512	0.00820	-0.0038	2180	4020
LMB36UU	6	1120	LMB36UU-AJ	6	1120	LMB36UU-OP	5	980	2	50.8	2	50.8	0.0035	0.8	0.0050	0.12	762003.0000	0.0090	0.22	40000181.600	0.012	0.300	3191781.67	0.012	0.300	0.10292.616	2187977.085	1.23	1.025	40	0.00717	0.01025	-0.00513	3820	7940	