

SS6800 Series

Vòng bi số	Dimensions (mm)			Ball NO	Complement Size	Maximum speed (r/min)		Weight Kg/pcs
	D	d	B			Grease	Oil	
S 683	7	3	3	7	1.2	45000	53000	0.0008
S 684	9	4	4	7	1.588	39000	48000	0.001
S 685	11	5	3	8	1.588	35000	45000	0.0019
S 686	13	6	5	8	2	33000	42000	0.0027
S 687	14	7	5	9	2	31000	40000	0.003
S 688	16	8	4	9	2.381	29000	38000	0.0038
S 689	17	9	4	11	2	28000	36000	0.004
S 6800	19	10	5	9	2.381	26000	34000	0.005
S 6801	21	12	7	9	2.381	22000	30000	0.006
S 6802	24	15	5	12	2.381	20000	28000	0.007
S 6803	26	17	5	14	2.381	19000	26000	0.008
S 6804	32	20	5	15	3.5	17000	22000	0.009
S 6805	37	25	7	13	3.5	15000	19000	0.022
S 6806	42	30	7	15	3.175	13000	17000	0.026
S 6807	47	35	7	19	3.5	11000	15000	0.029
S 6808	52	40	7	22	3.5	9000	13000	0.033
S 6809	58	45	7	22	3.96	9500	12000	0.04
S 6810	65	50	7	27	3.969	9000	11000	0.052
S 6811	72	55	9	21	4.763	8500	10000	0.083
S 6812	78	60	10	23	4.763	7500	9000	0.106
S 6813	85	65	10	23	5.953	7000	8500	0.125
S 6814	90	75	10	22	5.953	6700	8000	0.135
S 6815	95	75	10	24	5.953	6300	7500	0.145